

MASTEEL CNC HYDRAULIC BRAKES

 [Printable Version \(PDF\)](#)

MBHSA-14440

List Price:

Max. Capacity Tons	440
Max. Bending Length	14'
Distance between Frames	146"
Height of Bed	36"
Bed Below Floor	*- /24"
Depth of Throat	15 – ¾"
Length of Ram Stroke	10"
Fast Approach Speed IPM	190
Press Speed IPM	17
Fast Return Speed IPM	188
Max. Open Height	20-1/2"
Main Motor	40
Back gauge Travel	28"
Weight Lbs	60,000
Dimensions L x W x H	175x 72x130

*- /: without Hydraulic Crowning in Bed



STANDARD CONTROL FEATURES:

- ▣ **Standard SIEMENS TP-700 control with 6" Touch Screen display**
- ▣ **SIEMENS Two Axis CNC controls on back gauge and ram bending position**
 - Bosch-Rexroth Closed-loop proportional Hydraulic position control: repeatability standard at $\pm 0.0006"$, optional at $\pm 0.0004"$
 - Backgauge position control: Standard CNC backgauge: speed at 200 IPM as per Demo Video; repeatability at $\pm 0.003"$ Programmable backgauge retract feature
- ▣ **CNC bending angle control –Only inputs of bending angle, material thickness & die opening**
- ▣ **Two-way bending calibration controls** -allow inexperienced operator to achieve desired angles with no time consuming multiple test bends. Save on costly skilled labour and test bend material.
 - By correction of test-bending angle, control system automatically sets itself to achieve desired angle.
 - By correction of bending position calculated automatically by control system.
- ▣ **Dual ram position feedbacks with hydraulic Synchronized control compensates for uneven force on the bend**
- ▣ **Tool memory for quick recall of tool setup**
- ▣ **200 Job memory with average of 30 bends in each program**
- ▣ **Programmable pressure control**
- ▣ **Programmable ram delay control at bending position under adjustable pressure for bump bending or special heavy bending application**

- ☑ Maintenance plan auto-prompts service schedule
- ☑ Operating hour meter
- ☑ Operating prompts and Trouble shooting messages
- ☑ Inch / MM conversion

OPERATING FUNCTION:

- ☑ **Ram speed control:**
 - Rapid approach and return speeds insure more efficient production.
 - Slow bending speed for better control of bending accuracy
- ☑ **Ram stroke control:**
 - Programmable ram top stop limit for more efficient production
 - Programmable slow working speed position and second stop position
- ☑ **Four Operating Modes:**
 - Jog mode: inching control of ram for tool setup
 - Single mode: one full bend cycle per control input.
 - Double stop mode: excellent for sight bend operations.
 - Follow bend mode: easy to follow bending and ram return on large sheet or with crane handling

QUALITY & VALUE STANDARD EQUIPMENT:

- ☑ Two axis back gauge
 - One axis CNC control: X – axis
 - One axis manual adjustment: R – axis
 - Precision-made back gauge fingers
- ☑ Fully equipped with Masteel tooling and clamping system.
 - Floating-adjustable die clamping system for various die application
 - Hardened and precision ground tool steel gooseneck punch: 53-58RC; 100Ton/M(33Ton/Ft) capacity
 - Hardened and precision ground Masteel 10 openings, 4-way die: HB190-260.
- ☑ Masteel Crown Device for easy-adjusting tooling and machine wear intolerances
- ☑ Deeper throat depth with swing up clearance allows full length bend over bed up to 12"
- ☑ T- slotted bed for support arms or custom setups
- ☑ 2 - Front support arms

OPTIONAL EQUIPMENTS:

- ☑ Delem control DA-56 or up model
- ☑ Offline program software
- ☑ Manuel WILA Anti-Deflection system,
- ☑ Optional multi axis control: R, Z1, Z2 up to 6 axis
- ☑ Motorized Wila Anti-Deflection System which operates automatically with DNC unit according to tonnage applied,
- ☑ Hydraulic CNC crowning bed for automatic anti-deflection according to the tonnage
- ☑ Safety light curtain
- ☑ Laser protection system for die area,
- ☑ Hydraulic top and bottom tool holding system,
- ☑ Quick- set front sheet support arm with linear bearing rollers,
- ☑ Hydraulic oil coolant,
- ☑ Automatic slide greasing system,
- ☑ Special throat depth (500,600 and 750 mm),
- ☑ Special top and bottom tools

